

---

# Lubricant All Weather

---

Revision: 17/09/2015

Page 1 from 1

**Technical data**

Basis	Mixture of mineral oils with PTFE.
Consistency	Fluid
Density	Ca. 0,82 g/ml
Viscosity	210 cST at 20°C / 18,5 cSt at 100°C
Flashpoint	270 °C
Solubility in water	Not soluble
Volatile Organic Compounds (VOC)	80 %
Application temperature	5 °C → 30 °C

(\*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

**Product description**

Lubricant All Weather is a specially developed professional all weather chain lubricant based on synthetic oil with PTFE.

**Properties**

- Reduces friction in moving parts
- Rust and corrosion-resistant
- Reduces friction and wear
- Water-repellent
- Does not drip
- Low viscosity, easy to apply.
- Aerosol can be used in any angle (360°)

**Applications**

- Suitable for lubrication of bicycle chain, jockey wheels, cassette and chain rings.
- Suitable for all weather conditions.
- PTFE offers long-term protection against friction and wear.

**Packaging**

*Colour:* transparent

*Packaging:* 400 ml aerosol (net)

**Shelf life**

2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

**Substrates**

*Nature:* clean, dry, free of dust and grease.

**Application method**

*Application method:* Clean and degrease the parts in advance. Apply sufficient Lubricant All Weather. Wipe away excess product with a cloth.

**Health- and Safety Recommendations**

Take the usual labour hygiene into account.

**Liability**

The content of this technical data sheet is the result of tests, monitoring and experience. She is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions beyond our control, no liability under this publication are accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.