

Lubricant Wet Weather

Revision: 17/09/2015

Page 1 from 1

Technical data

Basis	Synthetic multipurpose EP-oil
Consistency	Fluid
Density	Ca. 0,99 g/ml
Viscosity	Ca. 460 cSt
Flashpoint	Ca. 246 °C
Application temperature	5 °C → 30 °C

(*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Product description

Lubricant Wet Weather is a specially developed professional wet weather chain lubricant based on synthetic oil.

Properties

- Reduces friction in moving parts
- Rust and corrosion-resistant
- Reduces friction and wear
- Water-repellent
- Does not drip
- Low viscosity, easy to apply.

Applications

- Suitable for lubrication of bicycle chain, jockey wheels, cassette and chain rings.
- Suitable for wet weather.

Packaging

Colour: transparent

Packaging: 100 ml

Shelf life

2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Substrates

Nature: clean, dry, free of dust and grease.

Application method

Application method: Clean and degrease the parts in advance. Apply sufficient Lubricant Wet Weather. Wipe away excess product with a cloth.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions beyond our control, no liability under this publication are accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.