



# **Mud Remover**

Revision: 16/07/2019 Page 1 from 1

#### **Technical data**

Basis	Water with specific detergents
Consistency	Fluid
Density	1,00 g/ml
Application temperature	5 °C → 35 °C

<sup>\*</sup> These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. \*\* This information relates to fully cured product.

## **Product description**

Mud Remover is a ready-to-use, professional, powerful cleaner for efficient cleaning of bicycle frames, wheels and handlebars.

# **Properties**

- Remove dried dirt, sand and dust
- Excellent cleaning properties
- Ready for use
- Not flammable
- Does not contain harmful solvents nor acids

# **Applications**

- Clean stubborn dirt and mud on bicycle frames, wheels and handlebars.
- Suitable for matt, painted and unpainted surfaces as well as carbon.

# **Packaging**

Colour: green Packaging: 1 L bottle

### Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

# Application method

Application method: Spray Mud Remover at the heavily polluted parts. Let the foam layer work for a few minutes. Stubborn dirt or mud can possibly be rubbed off with a sponge. Then thoroughly rinse off with plenty of water and dry with a dry cloth or blow dry.

**Health- and Safety Recommendations**Take the usual labour hygiene into account.

#### Remarks

- Mud Remover is slightly alkaline.
- We strongly recommend not to apply the product in full sunlight as it will dry very fast.

Remark: This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

 Soudal NV
 Everdongenlaan 18 - 20
 B-2300 Turnhout, Belgium

 Tel: +32 (0)14-42.42.31
 Fax: +32 (0)14-42.65.14
 www.soudal.com