

Silicone Paste

Revision: 16/07/2019

Page 1 from 1

Technical data

Basis	Silicone based paste
Consistency	Stable paste
Density	Ca. 1,00 g/ml
Viscosity	Ca. 1400 Pa.s
Application temperature	5 °C → 30 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

Silicone Paste is a specially developed professional protection paste with water-repellent effect.

Properties

- Water-repellent
- Rust and corrosion-resistant
- Eliminates cracking and squeaking.
- Contains no heavy metals.

Applications

- Suitable for protecting many surfaces, carbon, aluminum, titanium and plastic.

Packaging

Colour: transparent
Packaging: 200 ml

Shelf life

2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Substrates

Nature: clean, dry, dust-free.

Application method

Application method: Clean the substrate on beforehand. Apply sufficient Silicone Paste. Wipe away excess product with a cloth.

Health- and Safety Recommendations

Take the usual labour hygiene into account.

Remarks

- Silicone Paste is not suitable for lubrication of chain, bearings, headset and bottom bracket.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.